

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDC88004-3 G

光源	名 称	LEDランプ
	形 名	LDA5L-G-E17 /S/40W
	光束	440 lm × 3

前 面	
反射面	

保守率	良	0.67
	中	0.63
	否	0.56

効 率	F 	19 %
	F 	60 %
	F 	79 %
	器具 光束	1040 lm

--	--

最大取付間隔		備 考
A-A	1.37 H	
B-B	1.37 H	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	182		
10°	181		
20°	180		
30°	179		
40°	144		
50°	90		
60°	66		
70°	64		
80°	60		
90°	49		
100°	43		
110°	37		
120°	31		
130°	25		
140°	19		
150°	13		
160°	9		
170°	4		
180°	1		

反 射 率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		45	42	35	33	28	27	43	40	33	32	27	26	30	29	25	25	23	23	19	17		
0.80		54	49	43	40	36	34	51	47	41	39	34	33	38	36	32	31	30	29	25	23		
1.00		59	53	48	45	41	39	56	51	46	43	39	37	42	40	36	35	33	33	28	26		
1.25		65	57	54	50	46	44	61	55	51	48	45	42	47	44	41	39	38	36	32	29		
1.50		68	60	58	53	51	47	64	57	55	51	49	45	50	47	44	42	41	39	35	32		
2.00		74	65	65	58	58	53	70	62	62	56	55	51	56	52	50	48	46	44	40	36		
2.50		78	67	70	62	63	57	73	64	66	59	60	55	59	54	54	51	49	47	43	39		
3.00		81	69	73	64	67	60	76	66	69	62	64	57	62	57	57	53	52	49	45	41		
4.00		84	72	78	67	72	64	79	69	73	65	69	61	65	60	61	57	55	52	48	44		
5.00		87	73	81	70	76	66	81	70	76	67	72	64	68	62	64	59	57	55	51	46		
10.00		92	77	88	74	85	72	86	73	83	71	80	70	73	66	71	64	63	59	56	51		

