

東芝照明器具配光データシート

名 称		LE D照明器具		保守率	良	0.6 7			
形 名		LEDC88004-6 G			中	0.6 3			
					否	0.5 6			
光源	名 称	LE Dランプ		効 率	F 	1 9 %	最大取付間隔		
	形 名	LDA5L-G-E17 ／S／40W			F 	6 0 %			
	光 束	4 4 0 lm × 6			F 	7 9 %			
前 面				器具 光束	2 0 8 0 lm	A-A	1.3 7 H	備考	
反射面					B-B	1.3 7 H			

光度 (cd/1000lm)				反 射 率 (%)	天 井	80						70						50						30			20	0							
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70			50			30			70			50			30			50			30			30			10	0
							30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数				照 明 率 (×0.01)																															
0.60				45	42	35	33	28	27	43	40	33	32	27	26	30	29	25	25	23	23	19	17												
0.80				54	49	43	40	36	34	51	47	41	39	34	33	38	36	32	31	30	29	25	23												
1.00				59	53	48	45	41	39	56	51	46	43	39	37	42	40	36	35	33	33	28	26												
1.25				65	57	54	50	46	44	61	55	51	48	45	42	47	44	41	39	38	36	32	29												
1.50				68	60	58	53	51	47	64	57	55	51	49	45	50	47	44	42	41	39	35	32												
2.00				74	65	65	58	58	53	70	62	62	56	55	51	56	52	50	48	46	44	40	36												
2.50				78	67	70	62	63	57	73	64	66	59	60	55	59	54	54	51	49	47	43	39												
3.00				81	69	73	64	67	60	76	66	69	62	64	57	62	57	57	53	52	49	45	41												
4.00				84	72	78	67	72	64	79	69	73	65	69	61	65	60	61	57	55	52	48	44												
5.00				87	73	81	70	76	66	81	70	76	67	72	64	68	62	64	59	57	55	51	46												
10.00				92	77	88	74	85	72	86	73	83	71	80	70	73	66	71	64	63	59	56	51												

