

東芝照明器具配光データシート

名 称		L E D照明器具		保守率	良	0.6 7			
形 名		LEDC88004-8 G			中	0.6 3			
					否	0.5 6			
光源	名 称	L E Dランプ		効 率	F 	1 9 %		最大取付間隔	
	形 名	LDA5L-G-E17 /S/40W			F 	6 0 %			
	光 束	4 4 0 lm × 8			F 	7 9 %			
前 面				器具 光束				A-A	1.3 7 H
反射面								B-B	1.3 7 H

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50				30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70		50		30		50		30		30		10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10
				室指数	照 明 率 (×0.01)																							
0°	182			0.60	45	42	35	33	28	27	43	40	33	32	27	26	30	29	25	25	23	23	19	17				
10°	181			0.80	54	49	43	40	36	34	51	47	41	39	34	33	38	36	32	31	30	29	25	23				
20°	180			1.00	59	53	48	45	41	39	56	51	46	43	39	37	42	40	36	35	33	33	28	26				
30°	179			1.25	65	57	54	50	46	44	61	55	51	48	45	42	47	44	41	39	38	36	32	29				
40°	144			1.50	68	60	58	53	51	47	64	57	55	51	49	45	50	47	44	42	41	39	35	32				
50°	90			2.00	74	65	65	58	58	53	70	62	62	56	55	51	56	52	50	48	46	44	40	36				
60°	66			2.50	78	67	70	62	63	57	73	64	66	59	60	55	59	54	54	51	49	47	43	39				
70°	64			3.00	81	69	73	64	67	60	76	66	69	62	64	57	62	57	57	53	52	49	45	41				
80°	60			4.00	84	72	78	67	72	64	79	69	73	65	69	61	65	60	61	57	55	52	48	44				
90°	49			5.00	87	73	81	70	76	66	81	70	76	67	72	64	68	62	64	59	57	55	51	46				
100°	43			10.00	92	77	88	74	85	72	86	73	83	71	80	70	73	66	71	64	63	59	56	51				
110°	37																											
120°	31																											
130°	25																											
140°	19																											
150°	13																											
160°	9																											
170°	4																											
180°	1																											

