

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDC88005-3

光源	名 称	LEDランプ
	形 名	LDA5L-G-E17 /S/40W
	光束	440 lm × 3

前 面	
反射面	

保守率	良	0.67
	中	0.63
	否	0.56

効 率	F 	13 %
	F 	68 %
	F 	81 %
	器具 光束	1070 lm

--	--

最大取付間隔		備 考
A-A	1.53 H	
B-B	1.53 H	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	166		
10°	165		
20°	165		
30°	167		
40°	168		
50°	164		
60°	127		
70°	63		
80°	30		
90°	23		
100°	23		
110°	24		
120°	23		
130°	22		
140°	21		
150°	18		
160°	15		
170°	2		
180°	0		

反 射 率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		45	42	34	32	27	26	43	40	32	31	26	25	30	29	24	24	23	22	19	17		
0.80		55	50	43	40	35	34	52	48	41	39	34	33	38	37	32	31	30	30	26	23		
1.00		61	55	49	46	42	39	58	53	47	44	40	38	44	42	38	36	35	35	30	28		
1.25		68	60	56	52	48	45	64	58	54	50	47	44	50	47	44	42	41	40	36	33		
1.50		72	63	61	56	53	50	68	61	59	54	52	48	54	50	48	46	45	43	39	36		
2.00		79	68	69	62	62	57	74	66	66	60	60	55	61	56	56	52	52	50	46	42		
2.50		83	71	74	66	68	61	78	69	71	64	65	59	65	60	60	56	55	53	49	46		
3.00		86	73	78	69	72	64	81	71	75	66	69	63	68	62	64	59	59	56	52	49		
4.00		89	76	83	72	78	69	85	73	79	70	75	67	72	66	68	63	63	60	56	53		
5.00		92	77	87	74	82	71	87	75	82	72	78	69	74	68	71	66	65	62	59	55		
10.00		97	81	94	79	91	77	91	78	89	77	86	75	80	72	78	71	71	67	64	60		

