

東芝照明器具配光データシート

名 称		LED照明器具		保守率	良	0.67			
形 名		LEDC88005-6G			中	0.63			
					否	0.56			
光源	名 称	LEDランプ		効 率	F 	13%		最大取付間隔	
	形 名	LDA5L-G-E17 /S/40W			F 	68%			
	光束	440 lm × 6			F 	81%			
前 面				器具 光束		2130 lm		A-A	1.53H
反射面							B-B	1.53H	
								備考	

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70		50		30		70		50		30		50		30		30		10	0		
							30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数				照 明 率 (×0.01)																								
0.60				45	42	34	32	27	26	43	40	32	31	26	25	30	29	24	24	23	22	19	17					
0.80				55	50	43	40	35	34	52	48	41	39	34	33	38	37	32	31	30	30	26	23					
1.00				61	55	49	46	42	39	58	53	47	44	40	38	44	42	38	36	35	35	30	28					
1.25				68	60	56	52	48	45	64	58	54	50	47	44	50	47	44	42	41	40	36	33					
1.50				72	63	61	56	53	50	68	61	59	54	52	48	54	50	48	46	45	43	39	36					
2.00				79	68	69	62	62	57	74	66	66	60	60	55	61	56	56	52	52	50	46	42					
2.50				83	71	74	66	68	61	78	69	71	64	65	59	65	60	60	56	55	53	49	46					
3.00				86	73	78	69	72	64	81	71	75	66	69	63	68	62	64	59	59	56	52	49					
4.00				89	76	83	72	78	69	85	73	79	70	75	67	72	66	68	63	63	60	56	53					
5.00				92	77	87	74	82	71	87	75	82	72	78	69	74	68	71	66	65	62	59	55					
10.00				97	81	94	79	91	77	91	78	89	77	86	75	80	72	78	71	71	67	64	60					

