

東芝照明器具配光データシート

名称	直管形LEDランプシステム照明器具
形名	LER-22800-L D9+F-22123

保守率	良	0.81
	中	0.77
	否	0.72

光源	名称	LED (20タイプ)
	形名	LDL20T・N/9/12
	光束	1200 lm × 2

効率	F ◡	0%
	F ◣	67%
	F ○	67%
	器具光束	1620 lm

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前面	カバー (乳白)
反射面	塗装 (白)

備考	A-A	1.2 H
	B-B	1.2 H

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	250	250	250
10°	241	247	246
20°	225	232	230
30°	201	208	206
40°	169	177	174
50°	134	141	139
60°	96	103	100
70°	58	63	61
80°	22	26	24
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	70	50		
室指数	照明率 (×0.01)																			
0.60	43	39	33	31	27	27	41	38	33	31	27	26	32	30	27	26	26	26	23	22
0.80	51	46	41	39	35	34	49	45	41	38	35	34	39	38	34	33	34	33	30	29
1.00	56	50	47	43	40	38	54	49	46	43	40	38	44	42	39	37	38	37	34	33
1.25	61	54	52	48	46	43	59	53	51	47	45	43	49	46	44	42	43	41	38	37
1.50	64	57	56	51	50	46	62	56	55	50	49	46	52	49	48	45	46	45	42	40
2.00	70	61	63	56	57	52	67	60	61	55	56	52	58	54	54	51	52	50	47	46
2.50	73	63	67	59	62	55	70	62	65	58	60	55	61	57	58	54	55	53	51	49
3.00	75	65	70	61	65	58	73	64	68	60	63	57	64	59	61	56	58	55	53	52
4.00	78	67	74	64	70	61	76	66	72	63	68	61	67	62	65	60	61	59	57	55
5.00	80	68	76	66	73	63	77	67	74	65	71	63	69	63	67	62	64	60	59	57
10.00	84	70	82	69	80	68	81	69	79	68	77	67	74	67	73	66	68	65	63	62

