

東芝照明器具配光データシート

名称	直管形LEDランプシステム照明器具
形名	LER-22800-L D9+F-2273・G

保守率	良	0.86
	中	0.81
	否	0.72

最大取付間隔	
A-A	1.8 H
B-B	1.2 H

光源	名称	LED (20タイプ)
	形名	LDL20T・N/9/ 12
	光束	1200 lm × 2

効率	F ◡	0 %
	F ◣	83 %
	F ○	83 %
	器具光束	1990 lm

備考	
----	--

前面	ルーバー(アルミ・G)
反射面	塗装(白)

光度(cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	303	303	303
10°	299	298	300
20°	314	278	294
30°	366	249	305
40°	388	211	323
50°	197	161	258
60°	46	71	69
70°	18	17	16
80°	6	5	4
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80			70			50			30		20		0				
	壁	床	70		50		30		70		50		30		50		30			
			70	50	30	10	30	10	30	10	30	10	30	10	30	10	30			
室指数	照明率 (×0.01)																			
0.60	55	51	44	42	37	36	54	50	44	41	37	36	42	41	37	36	36	35	32	31
0.80	67	60	56	52	49	47	65	59	55	52	48	47	53	51	48	46	47	46	42	41
1.00	73	65	63	58	56	53	71	64	61	57	55	52	59	56	54	52	53	51	48	46
1.25	79	71	70	64	63	59	77	69	68	63	62	59	66	62	61	58	59	57	54	53
1.50	83	74	75	68	68	63	81	72	73	67	67	63	70	66	65	62	63	61	58	57
2.00	90	78	82	74	77	70	87	77	81	73	75	69	77	71	72	68	70	67	65	63
2.50	93	81	87	77	81	73	90	79	85	76	80	73	80	74	77	72	74	71	68	67
3.00	96	82	90	79	85	76	93	81	88	78	83	75	83	76	80	74	76	73	71	69
4.00	99	84	94	82	90	79	96	83	91	81	88	79	86	79	84	77	80	76	74	72
5.00	101	85	97	83	93	81	97	84	94	82	91	80	88	80	86	79	82	77	76	74
10.00	104	87	102	86	100	85	100	86	99	85	97	84	92	83	91	82	85	81	79	78

