

# 東芝照明器具配光データシート

名称	直管形LEDランプシステム照明器具
形名	LER-22800-L D9+F-2273・V

保守率	良	0.86
	中	0.81
	否	0.72

光源	名称	LED (20タイプ)
	形名	LDL20T・N/9/12
	光束	1200 lm × 2

効率	F ◡	0%
	F ◣	83%
	F ○	83%
	器具光束	1990 lm

最大取付間隔	
A-A	1.9 H
B-B	1.2 H

前面	ルーバー(アルミ・V)
反射面	塗装(白)

備考	A-A	1.9 H
	B-B	1.2 H

θ \ φ	光度(cd/1000lm)		
	A-A	B-B	C-C
0°	294	294	294
10°	287	289	289
20°	298	269	280
30°	381	240	298
40°	445	204	352
50°	225	158	312
60°	18	55	52
70°	2	2	2
80°	1	1	1
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率(%)	天井		80			70			50			30		20		0				
	壁	床	70	50	30	70	50	30	50	30	50	30	30	10	10	0	0			
室指数	照明率 (×0.01)																			
0.60	55	51	44	42	37	36	54	50	43	41	37	36	42	41	36	36	35	32	30	
0.80	67	61	56	53	49	47	65	60	55	52	49	47	54	51	48	46	47	46	43	41
1.00	73	66	63	59	56	53	71	65	62	58	56	53	60	57	54	52	53	52	49	47
1.25	80	71	71	65	64	60	78	70	69	64	63	60	67	63	61	59	60	58	55	54
1.50	84	74	76	69	69	64	82	73	74	68	68	64	71	67	66	63	64	62	59	58
2.00	91	79	83	75	78	71	88	78	81	74	76	70	78	72	74	69	71	68	66	65
2.50	94	81	88	77	83	74	91	80	85	77	81	74	81	75	78	73	75	72	69	68
3.00	96	83	91	80	86	77	93	82	88	79	84	76	84	77	81	75	77	74	72	70
4.00	99	85	95	82	91	80	96	83	92	81	89	79	87	80	84	78	80	77	75	73
5.00	101	85	97	83	94	82	98	84	94	83	91	81	89	81	86	79	82	78	76	75
10.00	104	87	102	86	100	85	101	86	99	85	97	84	92	83	91	83	86	81	80	78

