

東芝照明器具配光データシート

名 称		LED照明器具		保守率	良	0.67			
形 名		LEDP85021			中	0.63			
					否	0.56			
光源	名称	LEDランプ		効率	F 	0 %			
	形名	LDF7L-H-GX5 3/3			F 	85 %			
	光束	540 lm × 1			F 	85 %			
前 面					器具 光束	460 lm			
反射面					最大取付間隔		A-A	1.2 H	備考
						B-B	1.2 H		

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70		50		30		70		50		30		50		30		30		10	0		
							30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数				照 明 率 (×0.01)																								
0°				0.60	55	50	43	41	36	35	53	49	42	40	36	35	41	39	35	34	34	34	30	29				
10°				0.80	65	59	54	50	46	44	64	58	53	50	46	44	51	49	45	43	44	43	39	38				
20°				1.00	71	64	60	56	52	50	69	63	59	55	52	49	57	54	51	49	49	48	44	43				
30°				1.25	78	69	67	62	60	56	76	68	66	61	59	55	63	59	57	55	56	54	50	49				
40°				1.50	82	72	72	66	65	60	80	71	71	65	64	60	67	63	62	59	60	58	54	53				
50°				2.00	89	78	81	72	74	67	86	76	79	71	72	67	75	69	70	66	67	65	61	60				
60°				2.50	93	80	85	76	79	71	90	79	83	75	78	71	79	73	74	70	71	68	66	64				
70°				3.00	96	82	89	78	84	75	93	81	87	77	82	74	82	75	78	73	75	71	69	67				
80°				4.00	100	85	94	82	90	79	96	84	91	81	87	78	86	79	83	77	79	75	73	71				
90°				5.00	102	86	97	84	93	81	98	85	94	83	91	80	89	81	86	79	82	78	75	74				
100°				10.00	107	89	104	88	102	87	103	88	101	87	99	86	94	85	93	84	87	82	81	79				
110°																												
120°																												
130°																												
140°																												
150°																												
160°																												
170°																												
180°																												

