

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDP85021R

保守率	良	0.67
	中	0.63
	否	0.56

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

光源	名称	LEDランプ
	形名	LDF7L-H-GX5 3/3
	光束	540 lm × 1

効率	F ◡	0 %
	F ◣	85 %
	F ○	85 %
	器具 光束	460 lm

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

前面	
反射面	

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	329		
10°	326		
20°	305		
30°	269		
40°	225		
50°	176		
60°	128		
70°	75		
80°	12		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	1		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	10	0		
室指数	照明率 (×0.01)																								
0.60	55	50	43	41	36	35	53	49	42	40	36	35	41	39	35	34	34	34	30	29					
0.80	65	59	54	50	46	44	64	58	53	50	46	44	51	49	45	43	44	43	39	38					
1.00	71	64	60	56	52	50	69	63	59	55	52	49	57	54	51	49	49	48	44	43					
1.25	78	69	67	62	60	56	76	68	66	61	59	55	63	59	57	55	56	54	50	49					
1.50	82	72	72	66	65	60	80	71	71	65	64	60	67	63	62	59	60	58	54	53					
2.00	89	78	81	72	74	67	86	76	79	71	72	67	75	69	70	66	67	65	61	60					
2.50	93	80	85	76	79	71	90	79	83	75	78	71	79	73	74	70	71	68	66	64					
3.00	96	82	89	78	84	75	93	81	87	77	82	74	82	75	78	73	75	71	69	67					
4.00	100	85	94	82	90	79	96	84	91	81	87	78	86	79	83	77	79	75	73	71					
5.00	102	86	97	84	93	81	98	85	94	83	91	80	89	81	86	79	82	78	75	74					
10.00	107	89	104	88	102	87	103	88	101	87	99	86	94	85	93	84	87	82	81	79					

