

東芝照明器具配光データシート

名 称		LED照明器具		保守率	良	0.67			
形 名		LEDP85023			中	0.63			
					否	0.56			
光源	名 称	LEDランプ		効率	F 	19%		最大取付間隔	
	形 名	LDF7L-H-GX5 3/3			F 	56%			
	光束	540 lm × 1			F 	75%			
前 面				器具 光束	405 lm		A-A	0.8 H	備考
反射面							B-B	0.8 H	

光度 (cd/1000lm)				反射率 (%)	天井		80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10		0		
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
					室指数	照 明 率 (×0.01)																						
0°	152				0.60	39	36	28	26	21	20	37	34	26	25	20	20	24	23	18	18	17	16	13	10			
10°	161				0.80	47	42	35	33	28	27	44	40	33	31	26	25	30	29	24	23	22	21	17	15			
20°	95				1.00	52	47	40	37	33	31	48	44	38	36	31	30	34	32	28	27	25	25	20	17			
30°	81				1.25	57	51	46	42	38	36	54	48	44	40	36	34	39	37	33	31	30	29	24	21			
40°	100				1.50	61	54	50	46	42	39	57	51	47	44	40	38	42	40	36	35	33	32	27	23			
50°	103				2.00	67	59	58	51	50	46	63	56	54	49	47	44	48	45	43	40	38	37	32	28			
60°	98				2.50	71	61	62	55	55	50	66	58	59	53	52	48	52	48	47	44	42	40	35	31			
70°	87				3.00	74	63	66	58	59	53	69	60	62	55	56	51	55	50	50	47	44	43	38	34			
80°	72				4.00	78	66	71	62	65	57	73	63	67	59	62	55	59	54	55	51	49	46	42	38			
90°	58				5.00	80	68	75	64	69	60	75	65	70	61	65	58	61	56	58	53	51	49	45	40			
100°	46				10.00	86	72	82	69	79	67	80	69	77	67	74	64	68	61	65	59	58	55	51	46			
110°	36																											
120°	28																											
130°	23																											
140°	18																											
150°	12																											
160°	4																											
170°	4																											
180°	0																											

