

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDP88120

光源	名 称	LEDランプ
	形 名	LDA5N-G-E17 /S/40W
	光束	440 lm × 1

前 面	
反射面	

保守率	良	0.67
	中	0.63
	否	0.56

効 率	F 	19 %
	F 	56 %
	F 	75 %
	器具 光束	330 lm

--	--

最大取付間隔	
A-A	0.8 H
B-B	0.8 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	152		
10°	161		
20°	95		
30°	81		
40°	100		
50°	103		
60°	98		
70°	87		
80°	72		
90°	58		
100°	46		
110°	36		
120°	28		
130°	23		
140°	18		
150°	12		
160°	4		
170°	4		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		39	36	28	26	21	20	37	34	26	25	20	20	24	23	18	18	17	16	13	10		
0.80		47	42	35	33	28	27	44	40	33	31	26	25	30	29	24	23	22	21	17	15		
1.00		52	47	40	37	33	31	48	44	38	36	31	30	34	32	28	27	25	25	20	17		
1.25		57	51	46	42	38	36	54	48	44	40	36	34	39	37	33	31	30	29	24	21		
1.50		61	54	50	46	42	39	57	51	47	44	40	38	42	40	36	35	33	32	27	23		
2.00		67	59	58	51	50	46	63	56	54	49	47	44	48	45	43	40	38	37	32	28		
2.50		71	61	62	55	55	50	66	58	59	53	52	48	52	48	47	44	42	40	35	31		
3.00		74	63	66	58	59	53	69	60	62	55	56	51	55	50	50	47	44	43	38	34		
4.00		78	66	71	62	65	57	73	63	67	59	62	55	59	54	55	51	49	46	42	38		
5.00		80	68	75	64	69	60	75	65	70	61	65	58	61	56	58	53	51	49	45	40		
10.00		86	72	82	69	79	67	80	69	77	67	74	64	68	61	65	59	58	55	51	46		

