

東芝照明器具配光データシート

名 称		東芝LED器具				
形 名		LEKR415522N-LS9				
効 率	F 	0 %		保 守 率	良	0.86
	F 	100 %			中	0.81
	F 	100 %			否	0.72
	器具 光束		4900 lm		最大取付間隔	
前 面		カバー (乳白)		A-A		1.3 H
反射面		塗装 (白)		B-B		1.2 H
備 考						

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0				
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50			30			10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
					室指数	固有照明率 (×0.01)																									
0°	355	355	355		0.60	63	58	49	46	40	39	61	57	48	46	40	39	46	45	39	38	38	38	33	32						
10°	348	349	348		0.80	75	68	61	57	52	50	73	67	60	57	52	50	58	55	50	49	49	48	44	42						
20°	330	329	328		1.00	83	74	69	64	60	57	80	73	68	63	59	56	65	62	57	55	56	55	50	48						
30°	302	299	298		1.25	91	80	78	71	68	64	88	79	76	70	67	63	73	68	65	62	63	62	57	55						
40°	266	258	259		1.50	96	84	83	76	74	69	92	83	81	75	73	69	78	73	71	67	69	66	62	60						
50°	221	211	213		2.00	104	91	94	84	85	78	101	89	91	82	84	77	87	80	80	76	77	75	71	69						
60°	162	158	160		2.50	109	94	99	88	92	83	105	92	97	87	90	82	92	85	86	81	83	79	76	74						
70°	86	99	98		3.00	112	96	104	91	97	87	108	95	101	90	95	86	96	88	91	84	87	83	80	78						
80°	9	38	22		4.00	117	99	110	95	104	92	113	98	107	94	102	91	101	92	97	89	92	88	85	83						
90°	0	0	0		5.00	120	101	114	98	109	95	115	100	110	97	106	94	104	95	100	92	95	90	88	86						
100°	0	0	0		10.00	125	105	122	103	119	102	121	104	118	102	116	100	110	100	108	98	102	97	95	93						
110°	0	0	0																												
120°	0	0	0																												
130°	0	0	0																												
140°	0	0	0																												
150°	0	0	0																												
160°	0	0	0																												
170°	0	0	0																												
180°	0	0	0																												

