

■ 東芝照明器具配光データシート

名 称		L E D照明器具				
形 名		LEDP81007PW-LD				
効 率	F 	7 %		保守 率	良	0.67
	F 	93 %			中	0.63
	F 	100 %			否	0.56
	器具 光束	3570 lm		最大取付間隔		
前 面				備 考	A-A	1.3 H
反射面		塗装（白）			B-B	1.3 H

光度(cd/1000lm)				反射率 (%)	天井		80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70						50						30						10	0				
	0°	294	295			295	床	30		10		30		10		30		10		30		10		30		10		10	0
								30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
				室指数	固有照明率(×0.01)																								
0°				0.60	60	55	46	43	37	36	58	54	45	43	37	35	43	41	35	34	34	34	29	27					
10°				0.80	72	65	58	54	48	46	69	63	56	53	47	46	53	51	46	44	44	43	38	36					
20°				1.00	79	71	65	60	55	53	76	69	63	59	54	52	60	57	52	50	50	49	44	41					
30°				1.25	87	77	73	67	64	60	83	75	71	66	62	59	67	63	59	57	57	55	50	48					
40°				1.50	92	81	79	72	70	65	88	79	77	70	68	64	72	67	65	62	62	60	55	52					
50°				2.00	100	87	89	79	80	73	96	85	86	78	78	72	80	75	74	70	70	67	63	60					
60°				2.50	105	90	95	84	87	78	100	88	91	82	84	77	85	79	79	74	75	72	67	64					
70°				3.00	108	93	99	87	92	82	104	91	96	85	89	81	89	82	84	78	79	75	71	68					
80°				4.00	113	96	106	92	99	87	108	94	102	90	96	86	94	86	90	83	84	80	76	73					
90°				5.00	116	98	110	94	104	91	111	96	105	92	100	89	97	89	93	86	87	83	79	76					
100°				10.00	122	102	118	100	115	98	117	100	113	98	110	96	104	94	102	93	95	89	87	83					
110°																													
120°																													
130°																													
140°																													
150°																													
160°																													
170°																													
180°																													

