

東芝照明器具配光データシート

名 称		LED照明器具				
形 名		LEDP81009PL-LD				
効 率	F 	7 %		保 守 率	良	0.63
	F 	93 %			中	0.60
	F 	100 %			否	0.56
	器具 光束	3100 lm				
前 面				備 考		
反射面		塗装（白）				
		最大取付間隔				
		A-A	1.2 H			
		B-B	1.2 H			

光度 (cd/1000lm)				反 射 率 (%)	天井 壁 床	80						70						50						30		20	0		
$\theta \backslash \phi$	A-A	B-B	C-C			70			50			30			70			50			30			50		30		10	0
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
0°	350	350	350			固 有 照 明 率 (×0.01)																							
10°	342	342	342		室指数																								
20°	318	318	318		0.60	62	57	48	46	40	39	60	56	47	45	39	38	45	43	38	37	37	36	32	30				
30°	278	278	279		0.80	74	67	60	56	51	49	72	65	59	55	50	48	56	53	49	47	47	46	41	39				
40°	230	230	231		1.00	81	73	67	62	58	55	78	71	66	61	57	54	62	59	55	53	53	51	47	44				
50°	179	179	180		1.25	89	79	75	69	66	62	85	77	73	68	65	61	69	65	62	59	59	58	53	50				
60°	132	131	132		1.50	93	82	81	74	72	67	90	80	79	72	70	66	74	69	67	64	64	62	57	55				
70°	87	86	86		2.00	101	88	91	81	82	75	97	86	88	79	80	74	82	76	76	72	72	69	65	62				
80°	45	44	45		2.50	106	91	96	85	89	80	102	89	93	83	86	79	87	80	81	76	77	74	70	67				
90°	16	17	17		3.00	110	94	101	88	94	84	105	92	97	87	91	82	91	83	85	80	81	77	73	70				
100°	15	16	16		4.00	114	97	107	93	101	89	109	95	103	91	97	87	95	87	91	84	86	82	78	75				
110°	14	15	15		5.00	117	99	111	95	105	92	112	97	106	93	102	90	99	90	95	87	89	84	81	78				
120°	12	13	13		10.00	123	103	119	101	116	99	117	101	114	99	111	97	105	95	103	94	96	90	88	85				
130°	9	10	10																										
140°	7	7	7																										
150°	5	5	5																										
160°	3	3	2																										
170°	1	1	1																										
180°	1	1	1																										

