

東芝照明器具配光データシート

名 称		LED照明器具				
形 名		LEDP81027PW-LD				
効 率	F 	4 %		保守 率	良	0.6 7
	F 	9 6 %			中	0.6 3
	F 	1 0 0 %			否	0.5 6
	器具 光束	3 6 8 0 lm		最大取付間隔		
前 面				備 考		
反射面		塗装（白）				
		A-A	1. 3 H			
		B-B	1. 3 H			

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0							
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30		30		10	0			
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数					固 有 照 明 率 (×0.01)																													
0.60					63	58	49	47	41	40	61	57	48	46	40	39	47	45	39	38	38	38	33	32										
0.80					76	69	62	58	53	51	73	67	61	57	52	50	58	56	51	49	50	48	44	42										
1.00					83	75	70	65	61	58	80	73	68	64	60	57	65	62	58	56	56	55	50	48										
1.25					91	81	78	72	69	65	88	79	76	71	68	64	73	68	66	63	63	61	57	55										
1.50					96	84	84	76	75	70	92	83	82	75	74	69	78	73	71	68	68	66	62	59										
2.00					104	90	94	84	86	78	100	89	91	82	84	77	86	80	80	75	76	74	70	67										
2.50					108	94	99	88	92	83	104	92	96	86	90	82	91	84	85	80	81	78	74	72										
3.00					112	96	104	91	97	87	107	94	100	90	94	86	94	87	89	83	85	81	78	75										
4.00					116	99	110	95	104	91	112	97	106	93	101	90	99	90	95	88	90	85	82	80										
5.00					119	100	113	97	108	94	114	99	109	96	105	93	102	93	98	90	93	88	85	82										
10.00					124	104	121	102	118	100	119	102	116	100	114	99	108	97	106	96	99	93	91	88										

