

東芝照明器具配光データシート

名 称		LED照明器具				
形 名		LEDP82015PL-LD				
効 率	F 	7 %		保守 率	良	0.67
	F 	93 %			中	0.63
	F 	100 %			否	0.56
	器具 光束		4560 lm		最大取付間隔	
前 面		カバー（乳白）		備 考		
反射面		塗装（白）				
		A-A		1.3 H		
		B-B		1.3 H		

光度 (cd/1000lm)				反 射 率 (%)	天井	80			70			50		30	20	0
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	30	10	0
0°	345	345	345		床	30	10	30	10	30	10	30	10	30	10	0
10°	342	344	344		室指数 固有照明率 (×0.01)											
20°	331	333	334		0.60	64	59	50	48	42	41	62	57	49	47	41
30°	307	311	313		0.80	76	69	63	59	54	52	74	67	61	58	53
40°	258	265	278		1.00	83	75	70	65	61	58	80	73	68	64	60
50°	188	195	211		1.25	91	81	78	72	70	65	88	79	76	71	68
60°	117	123	125		1.50	96	84	84	76	76	70	92	82	82	75	74
70°	42	50	55		2.00	104	90	94	84	86	78	100	88	91	82	83
80°	27	29	27		2.50	108	93	99	88	92	83	104	91	96	86	89
90°	15	15	16		3.00	111	95	103	91	97	86	107	93	100	89	94
100°	14	14	15		4.00	116	98	109	94	103	91	111	96	105	93	100
110°	12	12	13		5.00	118	100	112	97	108	94	113	98	108	95	104
120°	11	11	12		10.00	123	103	120	101	117	100	118	101	115	99	113
130°	9	9	10													
140°	7	7	8													
150°	5	5	6													
160°	3	3	4													
170°	2	2	2													
180°	1	1	1													

