

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDP82015PW-LD

効 率	F 	7 %
	F 	93 %
	F 	100 %
	器具 光束	4920 lm

保守 率	良	0.67
	中	0.63
	否	0.56

前 面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備 考	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	345	345	345
10°	342	344	344
20°	331	333	334
30°	307	311	313
40°	258	265	278
50°	188	195	211
60°	117	123	125
70°	42	50	55
80°	27	29	27
90°	15	15	16
100°	14	14	15
110°	12	12	13
120°	11	11	12
130°	9	9	10
140°	7	7	8
150°	5	5	6
160°	3	3	4
170°	2	2	2
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																					
0.60		64	59	50	48	42	41	62	57	49	47	41	40	47	45	40	39	39	38	34	32		
0.80		76	69	63	59	54	52	74	67	61	58	53	51	59	56	51	50	50	49	44	42		
1.00		83	75	70	65	61	58	80	73	68	64	60	57	65	62	58	56	56	55	50	48		
1.25		91	81	78	72	70	65	88	79	76	71	68	64	72	68	66	63	63	61	57	54		
1.50		96	84	84	76	76	70	92	82	82	75	74	69	77	72	71	67	68	66	61	59		
2.00		104	90	94	84	86	78	100	88	91	82	83	77	85	79	79	75	76	73	69	66		
2.50		108	93	99	88	92	83	104	91	96	86	89	82	90	83	84	79	80	77	73	70		
3.00		111	95	103	91	97	86	107	93	100	89	94	85	93	86	88	82	84	80	76	74		
4.00		116	98	109	94	103	91	111	96	105	93	100	89	98	89	94	87	88	84	81	78		
5.00		118	100	112	97	108	94	113	98	108	95	104	92	100	91	97	89	91	86	83	80		
10.00		123	103	120	101	117	100	118	101	115	99	113	98	106	96	104	95	97	92	89	86		

