

東芝照明器具配光データシート

名 称		LED照明器具				
形 名		LEDP82027PW-LD				
効 率	F 	4 %		保守率	良	0.67
	F 	96 %			中	0.63
	F 	100 %			否	0.56
	器具 光束	4710 lm		最大取付間隔		
前 面				備考		
反射面		塗装（白）			A-A	1.3 H
				B-B	1.3 H	

光度 (cd/1000lm)				反 射 率 (%)	天井	80			70			50		30	20	0
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	30	10	0
0°	343	343	343	室 指 数	床	30	10	30	10	30	10	30	10	30	10	0
10°	338	339	339		固有照明率 (×0.01)											
20°	326	326	326	0.60	63	58	49	47	41	40	61	57	48	46	40	39
30°	303	304	304	0.80	76	69	62	58	53	51	73	67	61	57	52	50
40°	266	269	273	1.00	83	75	70	65	61	58	80	73	68	64	60	57
50°	206	209	225	1.25	91	81	78	72	69	65	88	79	76	71	68	64
60°	130	132	147	1.50	96	84	84	76	75	70	92	83	82	75	74	69
70°	58	61	64	2.00	104	90	94	84	86	78	100	89	91	82	84	77
80°	19	20	18	2.50	108	94	99	88	92	83	104	92	96	86	90	82
90°	12	11	11	3.00	112	96	104	91	97	87	107	94	100	90	94	86
100°	10	10	10	4.00	116	99	110	95	104	91	112	97	106	93	101	90
110°	8	8	9	5.00	119	100	113	97	108	94	114	99	109	96	105	93
120°	7	7	8	10.00	124	104	121	102	118	100	119	102	116	100	114	99
130°	6	5	7													
140°	5	4	6													
150°	3	3	4													
160°	2	2	3													
170°	1	1	2													
180°	1	1	1													

