

東芝照明器具配光データシート

名 称		LED照明器具				
形 名		LEDP82029PW-LD				
効 率	F 	4 %		保守率	良	0.67
	F 	96 %			中	0.63
	F 	100 %			否	0.56
	器具 光束	4710 lm		最大取付間隔		
前 面				備考	A-A	1.3 H
反射面		塗装（白）				B-B

光度 (cd/1000lm)				反 射 率 (%)	天井 壁 床	80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0		
0°	343	343	343			30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
10°	338	339	339																								
20°	326	326	326	固 有 照 明 率 (×0.01)																							
30°	303	304	304	0.60	63	58	49	47	41	40	61	57	48	46	40	39	47	45	39	38	38	38	33	32			
40°	266	269	273	0.80	76	69	62	58	53	51	73	67	61	57	52	50	58	56	51	49	50	48	44	42			
50°	206	209	225	1.00	83	75	70	65	61	58	80	73	68	64	60	57	65	62	58	56	56	55	50	48			
60°	130	132	147	1.25	91	81	78	72	69	65	88	79	76	71	68	64	73	68	66	63	63	61	57	55			
70°	58	61	64	1.50	96	84	84	76	75	70	92	83	82	75	74	69	78	73	71	68	68	66	62	59			
80°	19	20	18	2.00	104	90	94	84	86	78	100	89	91	82	84	77	86	80	80	75	76	74	70	67			
90°	12	11	11	2.50	108	94	99	88	92	83	104	92	96	86	90	82	91	84	85	80	81	78	74	72			
100°	10	10	10	3.00	112	96	104	91	97	87	107	94	100	90	94	86	94	87	89	83	85	81	78	75			
110°	8	8	9	4.00	116	99	110	95	104	91	112	97	106	93	101	90	99	90	95	88	90	85	82	80			
120°	7	7	8	5.00	119	100	113	97	108	94	114	99	109	96	105	93	102	93	98	90	93	88	85	82			
130°	6	5	7	10.00	124	104	121	102	118	100	119	102	116	100	114	99	108	97	106	96	99	93	91	88			
140°	5	4	6																								
150°	3	3	4																								
160°	2	2	3																								
170°	1	1	2																								
180°	1	1	1																								

