

東芝照明器具配光データシート

名 称	LED照明器具					
形 名	LEDP82033PW-LD					
効 率	F 	1 2 %		保守 率	良	0.63
	F 	8 8 %			中	0.60
	F 	1 0 0 %			否	0.56
	器具 光束	4 3 5 0 lm		最大取付間隔		
前 面				備 考		
反射面	塗装 (白)					
			A-A	1.2 H		
			B-B	1.2 H		

光度 (cd/1000lm)				反 射 率 (%)	天 井 壁 床	80						70						50						30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C			70			50			30			70			50			30			50		30		30	10	0
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
						固 有 照 明 率 (×0.01)																								
0°	319	319	319	室指数	0.60	61	56	47	44	38	37	58	54	45	43	37	36	43	41	36	35	35	34	29	27					
10°	313	311	312		0.80	72	66	58	55	49	47	69	63	56	53	48	46	53	51	46	45	44	43	38	36					
20°	291	288	290		1.00	79	71	65	60	56	53	76	69	63	59	55	52	59	56	52	50	49	48	43	41					
30°	255	251	255		1.25	87	77	73	67	64	60	83	74	71	65	62	59	66	62	59	56	56	54	49	46					
40°	211	208	212		1.50	91	80	79	71	69	64	87	78	76	70	67	63	71	66	64	61	60	58	53	50					
50°	165	164	166		2.00	99	86	88	79	80	73	95	84	85	77	77	71	79	73	72	68	68	65	61	57					
60°	124	126	124		2.50	104	90	94	83	86	77	99	87	90	81	83	76	83	77	78	73	73	70	65	62					
70°	89	90	87		3.00	107	92	99	86	91	81	102	89	94	84	88	80	87	80	82	76	76	73	69	65					
80°	55	55	54		4.00	112	95	105	91	98	86	107	93	100	88	95	85	92	84	88	81	81	77	73	70					
90°	25	25	26		5.00	115	97	109	93	103	90	109	95	104	91	99	88	95	87	91	84	84	80	76	73					
100°	24	24	25		10.00	121	101	117	99	114	97	115	99	112	97	109	95	102	92	100	90	91	86	83	79					
110°	23	23	24																											
120°	21	20	22																											
130°	17	16	18																											
140°	12	12	14																											
150°	9	8	10																											
160°	6	5	6																											
170°	3	3	3																											
180°	2	2	2																											

