


東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEKR416692L-LS9

効 率	F 	0 %	保 守 率	良	0.86
	F 	100 %		中	0.81
	F 	100 %		否	0.72
	器具 光束	5350 lm	最大取付間隔		

前 面		A-A	1.3 H
反射面	塗装 (白)	B-B	1.2 H



備 考	
--------	--

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50	30	30	10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
						固 有 照 明 率 (×0.01)																						
0°	395	395	395	室指数	0.60	66	60	52	49	44	42	64	59	51	49	43	42	50	48	43	42	42	41	37	35			
10°	388	388	388		0.80	78	71	65	61	56	54	76	70	64	60	56	54	62	59	55	53	54	52	48	46			
20°	370	367	368		1.00	85	77	72	67	64	60	83	75	71	66	63	60	69	65	61	59	60	58	54	52			
30°	342	332	336		1.25	93	83	81	74	72	67	90	81	79	73	71	67	76	71	69	66	67	65	61	59			
40°	285	287	293		1.50	98	86	86	78	78	72	95	85	84	78	77	72	81	76	74	71	72	70	66	64			
50°	181	234	228		2.00	106	92	96	86	88	81	102	91	94	85	86	80	89	83	83	79	80	77	74	72			
60°	59	174	129		2.50	110	95	102	90	94	85	107	94	99	89	92	84	94	87	89	83	85	82	78	76			
70°	42	108	42		3.00	114	97	106	93	99	89	110	96	103	92	97	88	97	90	93	86	89	85	82	80			
80°	23	41	24		4.00	118	100	111	96	106	93	114	99	108	95	103	92	102	93	98	91	93	89	86	84			
90°	0	0	0		5.00	120	102	115	99	110	96	116	100	111	98	107	95	105	95	101	93	96	91	89	87			
100°	0	0	0		10.00	125	105	122	103	120	102	121	104	118	102	116	101	111	100	109	99	102	97	95	93			
110°	0	0	0																									
120°	0	0	0																									
130°	0	0	0																									
140°	0	0	0																									
150°	0	0	0																									
160°	0	0	0																									
170°	0	0	0																									
180°	0	0	0																									

