

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB87920L(S)-LS

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	485 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	340	340	340
10°	335	336	336
20°	318	322	322
30°	291	295	295
40°	253	258	258
50°	206	212	211
60°	152	160	158
70°	93	102	99
80°	35	42	40
90°	0	1	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0	
室指数	固有照明率 (×0.01)																								
0.60	63	58	48	46	40	38	61	56	47	45	39	38	46	44	38	38	38	37	33	31					
0.80	75	68	61	57	51	49	73	67	59	56	51	49	57	55	50	48	49	48	43	41					
1.00	82	74	68	63	59	56	80	72	67	62	58	55	64	61	56	54	55	54	49	47					
1.25	90	80	77	70	67	63	87	78	75	69	66	63	72	68	64	62	62	61	56	54					
1.50	95	84	83	75	73	68	92	82	81	74	72	68	77	72	70	66	68	65	61	59					
2.00	104	90	93	83	84	77	100	89	90	82	82	76	86	80	79	75	76	74	70	67					
2.50	108	93	99	87	91	82	105	92	96	86	89	81	91	84	85	80	82	78	75	73					
3.00	112	96	103	91	96	86	108	94	100	89	94	85	95	87	90	84	86	82	79	77					
4.00	117	99	110	95	104	91	112	98	106	94	101	90	100	92	96	89	91	87	84	82					
5.00	119	101	114	98	108	94	115	100	110	96	105	93	103	94	100	92	95	90	87	85					
10.00	125	105	122	103	119	101	121	104	118	102	115	100	110	100	108	98	102	96	94	92					

