


東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB87937L (K) -LS



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	220 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	352	352	352
10°	346	346	346
20°	328	326	327
30°	298	296	297
40°	259	256	258
50°	212	208	210
60°	158	153	156
70°	99	93	96
80°	40	32	36
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	1	0	0

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	0		
室指数	固有照明率 (×0.01)																								
0.60	63	58	49	46	40	39	61	57	48	46	40	39	46	45	39	38	38	38	33	31					
0.80	75	68	61	57	52	50	73	67	60	57	51	49	58	55	50	49	49	48	43	42					
1.00	83	74	69	64	59	56	80	73	67	63	58	56	65	61	57	55	56	54	50	48					
1.25	90	80	77	71	68	63	87	79	75	70	67	63	72	68	65	62	63	61	57	54					
1.50	95	84	83	75	74	69	92	82	81	74	73	68	77	73	70	67	68	66	62	59					
2.00	104	90	93	83	85	77	100	89	91	82	83	77	86	80	80	75	77	74	70	68					
2.50	109	94	99	88	91	82	105	92	96	86	89	82	91	84	86	80	82	79	75	73					
3.00	112	96	104	91	97	86	108	95	101	90	94	85	95	88	90	84	86	82	79	77					
4.00	117	99	110	95	104	91	113	98	107	94	101	91	100	92	96	89	92	87	84	82					
5.00	120	101	114	98	109	95	115	100	110	97	106	94	104	94	100	92	95	90	87	85					
10.00	125	105	122	103	119	101	121	104	118	102	115	100	110	100	108	98	102	96	94	92					

