

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDG87911L (S) -LS

効 率	F 	35 %
	F 	65 %
	F 	100 %
	器具 光束	475 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前 面	
反射面	

最大取付間隔	
A-A	1.8 H
B-B	1.8 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	98		
10°	104		
20°	110		
30°	114		
40°	117		
50°	116		
60°	110		
70°	101		
80°	89		
90°	79		
100°	76		
110°	70		
120°	63		
130°	53		
140°	43		
150°	30		
160°	15		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		固有照明率 (×0.01)																						
0.60		51	47	36	34	27	26	47	44	34	32	26	25	30	28	23	22	20	19	14	11			
0.80		61	56	46	43	36	35	57	52	43	41	34	33	37	36	30	29	26	25	20	16			
1.00		68	61	53	49	43	40	63	57	49	46	40	38	43	40	35	34	31	30	24	19			
1.25		76	67	61	56	50	47	70	63	57	52	47	44	49	46	41	40	36	35	28	23			
1.50		80	71	66	60	56	52	74	66	62	57	52	49	53	50	46	44	40	38	32	26			
2.00		89	77	76	68	66	60	82	72	71	64	62	57	61	56	54	51	46	45	38	32			
2.50		94	81	82	72	73	65	86	76	76	68	68	62	65	60	59	55	51	49	42	35			
3.00		98	84	87	76	78	70	90	79	81	72	73	66	69	63	63	59	54	52	45	38			
4.00		103	87	94	81	86	75	94	82	87	77	80	71	74	68	69	64	59	56	50	42			
5.00		106	89	98	84	91	79	97	84	91	79	85	75	77	71	73	67	62	59	53	45			
10.00		113	94	108	91	104	88	104	89	100	86	96	84	85	77	82	75	70	66	61	53			

