


# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDS87900L (K) -LS



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	475 lm

保守 率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	358		
10°	353		
20°	332		
30°	297		
40°	253		
50°	203		
60°	150		
70°	96		
80°	43		
90°	5		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	1		
180°	1		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0								
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0								
室指数	固有照明率 (×0.01)																								
0.60	63	58	49	46	40	39	61	57	48	46	40	39	47	45	39	38	39	38	33	32					
0.80	75	69	61	57	52	50	73	67	60	57	51	49	58	55	50	49	49	48	44	42					
1.00	83	74	69	64	59	56	80	73	67	63	58	56	65	61	57	55	56	54	50	47					
1.25	90	80	77	71	68	63	87	79	75	70	67	63	72	68	65	62	63	61	56	54					
1.50	95	84	83	75	74	68	92	82	81	74	72	68	77	72	70	67	68	66	61	59					
2.00	104	90	93	83	84	77	100	89	90	82	83	76	86	80	79	75	76	74	70	67					
2.50	108	94	99	87	91	82	105	92	96	86	89	81	91	84	85	80	82	78	74	72					
3.00	112	96	103	91	96	86	108	94	100	89	94	85	95	87	90	83	86	82	78	76					
4.00	117	99	110	95	104	91	112	98	106	94	101	90	100	91	96	88	91	87	84	82					
5.00	119	101	114	97	108	94	115	100	110	96	105	93	103	94	99	91	94	90	87	85					
10.00	125	105	122	103	119	101	121	103	118	102	115	100	110	99	108	98	102	96	94	92					

