

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDG87913L (K) -LS

効 率	F 	1 5 %
	F 	8 5 %
	F 	1 0 0 %
	器具 光束	2 7 5 lm

保 守 率	良	0.63
	中	0.60
	否	0.56

前 面	
反射面	

最大取付間隔	
A-A	3.8 H
B-B	3.8 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	35		
10°	38		
20°	47		
30°	47		
40°	227		
50°	240		
60°	194		
70°	130		
80°	84		
90°	54		
100°	39		
110°	29		
120°	22		
130°	16		
140°	12		
150°	9		
160°	6		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																					
0.60		47	43	30	29	21	20	44	41	29	28	20	19	26	25	18	17	16	16	10	8		
0.80		59	53	41	39	30	29	55	50	40	37	29	28	36	34	27	26	25	24	18	15		
1.00		67	60	50	46	39	37	63	57	48	45	37	35	43	41	34	33	32	31	25	21		
1.25		76	67	60	55	48	45	71	64	57	53	46	44	52	49	43	41	39	38	32	28		
1.50		82	72	66	60	55	51	77	69	63	58	53	49	57	54	49	46	45	43	37	33		
2.00		91	79	78	69	67	61	86	76	74	67	64	59	67	62	59	56	54	52	46	42		
2.50		97	84	85	75	75	67	91	80	81	72	72	65	73	67	66	62	60	58	52	48		
3.00		101	87	90	79	81	72	96	84	86	76	78	70	78	71	71	66	65	62	57	52		
4.00		107	91	98	85	90	79	101	88	93	82	86	77	84	77	78	72	72	68	63	58		
5.00		110	93	103	88	96	83	104	90	97	85	91	81	88	80	83	76	76	72	67	62		
10.00		118	99	113	96	109	93	112	96	107	93	104	90	97	87	94	85	85	80	76	72		

