

東芝照明器具配光データシート

名 称		屋外LEDガーデンライト					
形 名		LEDG87906L (S) -LS					
効 率	F 	5 0 %		保 守 率	良	0.6 3	
	F 	5 0 %			中	0.6 0	
	F 	1 0 0 %			否	0.5 6	
	器具 光束	3 3 5 lm		最大取付間隔			
前 面		グローブ (乳白)		備 考		上部カバーあり	
反射面							
		A-A		6. 3		H	
		B-B		6. 3		H	

光度 (cd/1000lm)				反 射 率 (%)	天井	80			70			50		30	20	0
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	30	10	0
0°	5				床	30	10	30	10	30	10	30	10	30	10	0
10°	14				室指数 固有照明率 (×0.01)											
20°	31				0.60	46	43	32	30	23	22	42	39	29	27	21
30°	47				0.80	56	51	40	38	30	29	50	46	37	35	28
40°	63				1.00	62	56	47	44	37	35	56	51	43	40	33
50°	77				1.25	70	62	55	50	44	41	63	56	49	46	40
60°	88				1.50	74	66	60	54	49	46	67	60	54	50	45
70°	96				2.00	83	72	69	62	59	54	74	66	63	57	53
80°	103				2.50	87	75	75	66	65	59	78	69	68	61	59
90°	105				3.00	91	78	80	70	71	63	82	72	72	65	64
100°	102				4.00	96	82	87	75	79	69	87	75	79	69	71
110°	98				5.00	100	84	91	78	84	73	90	78	83	72	76
120°	88				10.00	107	90	102	86	97	82	97	83	92	80	88
130°	77															
140°	63															
150°	47															
160°	30															
170°	13															
180°	5															

