

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDD-15021W

光源	名称	
	形名	LED
	光束	1250 lm × 1

前 面	
反射面	

保守率	良	0.81
	中	0.77
	否	0.68

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	1250 lm

--	--

最大取付間隔		備 考
A-A	0.3 H	
B-B	0.3 H	

光度 (cd/1000lm)			
0°	8960	25°	213
1°		30°	99
2°		35°	49
3°		40°	29
4°		45°	18
5°	6514	50°	11
6°		55°	7
7°		60°	4
8°		65°	2
9°		70°	0
10°	2795	75°	0
11°		80°	0
12°		85°	0
13°		90°	0
14°			
15°	1051		
16°			
17°			
18°			
19°			
20°	452		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		照 明 率 (×0.01)																						
0.60		98	90	90	86	86	83	97	90	90	86	85	83	88	85	85	83	84	82	81	80			
0.80		104	95	97	91	92	88	103	94	96	90	91	88	94	90	90	87	89	87	85	84			
1.00		109	97	101	94	96	91	107	97	100	93	95	91	98	92	94	90	92	90	88	87			
1.25		111	99	104	95	98	92	109	98	102	94	97	92	99	93	95	91	93	90	89	88			
1.50		113	99	106	96	100	93	110	99	104	95	99	93	100	94	97	92	94	91	89	88			
2.00		116	101	109	98	104	95	113	100	107	97	102	95	103	96	99	93	96	92	90	89			
2.50		119	102	113	99	108	97	115	101	110	99	106	96	105	97	102	95	98	94	92	91			
3.00		121	103	115	101	111	99	117	102	112	100	109	98	107	99	104	97	100	96	94	92			
4.00		124	105	120	104	116	102	120	104	116	103	113	101	110	101	108	100	103	98	97	95			
5.00		126	107	123	106	120	105	122	106	119	105	117	104	113	103	111	102	106	101	99	98			
10.00		131	109	130	110	129	110	126	108	126	109	125	109	118	107	118	107	111	105	105	103			

