

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT750452W-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	4400 lm

保 守 率	良	0.81
	中	0.77
	否	0.68

前 面	
反射面	塗装 (白)

最大取付間隔	
A-A	1.2 H
B-B	1.3 H

--	--

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	330	330	330
10°	323	325	324
20°	304	310	307
30°	273	286	279
40°	233	255	243
50°	188	221	201
60°	137	177	159
70°	84	129	109
80°	32	72	58
90°	0	0	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		固有照明率 (×0.01)																						
0.60		61	57	47	45	38	37	60	55	46	44	38	37	45	43	37	36	37	36	31	30			
0.80		74	67	59	55	50	48	71	65	58	55	49	47	56	53	48	47	47	46	41	39			
1.00		81	72	66	62	57	54	78	71	65	61	56	53	62	59	55	53	53	52	47	45			
1.25		89	79	75	69	65	61	86	77	73	68	64	61	70	66	62	60	60	59	54	52			
1.50		94	83	81	73	71	66	90	81	79	72	70	66	75	70	68	65	66	63	59	57			
2.00		102	89	91	81	82	75	99	87	88	80	80	74	84	78	77	73	74	72	67	65			
2.50		107	92	97	86	89	80	103	91	94	85	87	79	89	82	83	78	80	77	73	70			
3.00		111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	77	75			
4.00		116	98	108	94	102	90	111	97	105	93	99	89	99	90	94	87	90	85	82	80			
5.00		118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	89	86	84			
10.00		125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91			

