

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT771652L-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	5550 lm

保 守 率	良	0.81
	中	0.77
	否	0.68

前 面	バツフル (白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備 考	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	347	347	347
10°	342	335	340
20°	327	310	319
30°	302	274	287
40°	269	230	247
50°	233	180	202
60°	185	128	153
70°	133	75	98
80°	72	27	43
90°	0	3	4
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反 射 率 (%)	天井 壁 床	80			70			50			30		20	0
		70	50	30	70	50	30	50	30	50	30	30	10	0
		30	10	30	10	30	10	30	10	30	10	30	10	0
室指数		固有照明率 (×0.01)												
0.60		62	57	48	45	39	38	60	56	47	45	39	38	46
0.80		74	68	60	56	51	49	72	66	59	56	50	48	57
1.00		82	73	68	63	58	55	79	72	66	62	57	55	63
1.25		89	79	76	70	66	62	86	78	74	69	65	62	71
1.50		94	83	82	74	72	67	91	82	80	73	71	67	76
2.00		103	89	92	82	83	76	99	88	89	81	81	75	85
2.50		108	93	98	86	90	81	104	91	95	85	88	80	90
3.00		111	95	103	90	95	85	107	94	99	89	93	84	94
4.00		116	99	109	94	103	90	112	97	105	93	100	89	99
5.00		119	100	113	97	107	94	114	99	109	96	104	93	102
10.00		125	104	121	102	118	101	120	103	117	101	114	100	109

