


■ 東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT425323W-LS9

効 率	F 	0 %	保守率	良	0.86
	F 	100 %		中	0.81
	F 	100 %		否	0.72
	器具光束	2850 lm	最大取付間隔		

前 面	カバー（乳白）	A - A	1. 3	H
反射面	塗装（白）	B - B	1. 2	H

備考	
----	--

光度(cd/1000lm)				反射率 (%)	天井		80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70						50						30						10	0			
						70		50		30		70		50		30		50		30		30	10	0				
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
				室指数	固有照明率(×0.01)																							
0°				0.60	61	56	47	44	38	37	60	55	46	44	38	37	45	43	37	36	36	36	31	29				
10°				0.80	73	67	59	55	49	47	71	65	58	54	49	47	56	53	48	46	47	46	41	39				
20°				1.00	81	72	66	61	57	54	78	71	65	61	56	53	62	59	54	52	53	52	47	45				
30°				1.25	88	78	75	68	65	61	85	77	73	67	64	60	70	66	62	59	60	58	54	51				
40°				1.50	93	82	81	73	71	66	90	81	79	72	70	65	75	70	68	64	65	63	59	56				
50°				2.00	102	89	91	81	82	75	98	87	88	80	80	74	84	78	77	73	74	71	67	65				
60°				2.50	107	92	97	86	89	80	103	91	94	84	87	79	89	82	83	78	79	76	72	70				
70°				3.00	111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	76	74				
80°				4.00	115	98	108	94	102	89	111	97	105	92	99	89	99	90	94	87	89	85	82	80				
90°				5.00	118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	88	86	83				
100°				10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91				
110°																												
120°																												
130°																												
140°																												
150°																												
160°																												
170°																												
180°																												

