

東芝照明器具配光データシート


名 称	東芝LED器具
形 名	LEKR415403N-LS9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		3800 lm

保守率	良	0.86
	中	0.81
	否	0.72

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反射率 (%)	天井		80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0			
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
						固有照明率 (×0.01)																						
0°	355	355	355	室指数	0.60	63	58	49	46	40	39	61	57	48	46	40	39	46	45	39	38	38	38	33	32			
10°	348	349	348	0.80	75	68	61	57	52	50	73	67	60	57	52	50	58	55	50	49	49	48	44	42				
20°	330	329	328	1.00	83	74	69	64	60	57	80	73	68	63	59	56	65	62	57	55	56	55	50	48				
30°	302	299	298	1.25	91	80	78	71	68	64	88	79	76	70	67	63	73	68	65	62	63	62	57	55				
40°	266	258	259	1.50	96	84	83	76	74	69	92	83	81	75	73	69	78	73	71	67	69	66	62	60				
50°	221	211	213	2.00	104	91	94	84	85	78	101	89	91	82	84	77	87	80	80	76	77	75	71	69				
60°	162	158	160	2.50	109	94	99	88	92	83	105	92	97	87	90	82	92	85	86	81	83	79	76	74				
70°	86	99	98	3.00	112	96	104	91	97	87	108	95	101	90	95	86	96	88	91	84	87	83	80	78				
80°	9	38	22	4.00	117	99	110	95	104	92	113	98	107	94	102	91	101	92	97	89	92	88	85	83				
90°	0	0	0	5.00	120	101	114	98	109	95	115	100	110	97	106	94	104	95	100	92	95	90	88	86				
100°	0	0	0	10.00	125	105	122	103	119	102	121	104	118	102	116	100	110	100	108	98	102	97	95	93				
110°	0	0	0																									
120°	0	0	0																									
130°	0	0	0																									
140°	0	0	0																									
150°	0	0	0																									
160°	0	0	0																									
170°	0	0	0																									
180°	0	0	0																									

