

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKR415693YW-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	6300 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反 射 率 (%)	天井		80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70						50						30						10	0			
						70		50		30		70		50		30		50		30		30	10	0				
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
				室指数	固 有 照 明 率 (×0.01)																							
0°				63	58	49	46	40	39	61	57	48	46	40	39	46	45	39	38	38	38	33	32					
10°				75	68	61	57	52	50	73	67	60	57	52	50	58	55	50	49	49	48	44	42					
20°				83	74	69	64	60	57	80	73	68	63	59	56	65	62	57	55	56	55	50	48					
30°				91	80	78	71	68	64	88	79	76	70	67	63	73	68	65	62	63	62	57	55					
40°				96	84	83	76	74	69	92	83	81	75	73	69	78	73	71	67	69	66	62	60					
50°				104	91	94	84	85	78	101	89	91	82	84	77	87	80	80	76	77	75	71	69					
60°				109	94	99	88	92	83	105	92	97	87	90	82	92	85	86	81	83	79	76	74					
70°				112	96	104	91	97	87	108	95	101	90	95	86	96	88	91	84	87	83	80	78					
80°				117	99	110	95	104	92	113	98	107	94	102	91	101	92	97	89	92	88	85	83					
90°				120	101	114	98	109	95	115	100	110	97	106	94	104	95	100	92	95	90	88	86					
100°				125	105	122	103	119	102	121	104	118	102	116	100	110	100	108	98	102	97	95	93					
110°																												
120°																												
130°																												
140°																												
150°																												
160°																												
170°																												
180°																												

