

東芝照明器具配光データシート


名 称	東芝LED器具
形 名	LEKR430203YL-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	1730 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0		
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
						固有照明率 (×0.01)																					
0°	330	330	330	室指数	0.60	61	57	47	45	38	37	60	55	46	44	38	37	45	43	37	36	37	36	31	30		
10°	325	324	324		0.80	74	67	59	55	50	48	71	65	58	55	49	47	56	53	48	47	47	46	41	39		
20°	310	305	307		1.00	81	73	67	62	57	54	78	71	65	61	56	54	63	59	55	53	53	52	47	45		
30°	285	276	280		1.25	89	79	75	69	65	61	86	77	73	68	64	61	70	66	63	60	61	59	54	52		
40°	254	237	245		1.50	94	83	81	74	72	67	91	81	79	73	70	66	75	71	68	65	66	64	59	57		
50°	222	192	204		2.00	102	89	91	82	83	75	99	87	89	80	81	75	84	78	78	73	75	72	68	66		
60°	180	140	165		2.50	107	93	97	86	89	81	103	91	95	85	87	80	90	83	84	78	80	77	73	71		
70°	126	85	113		3.00	111	95	102	90	95	85	107	94	99	88	93	84	94	86	88	82	84	81	77	75		
80°	46	31	54		4.00	116	98	109	94	103	90	112	97	105	93	100	89	99	91	95	87	90	86	83	81		
90°	0	0	0		5.00	119	100	113	97	107	93	114	99	109	96	104	92	102	93	99	91	94	89	86	84		
100°	0	0	0		10.00	125	104	122	102	118	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92		
110°	0	0	0																								
120°	0	0	0																								
130°	0	0	0																								
140°	0	0	0																								
150°	0	0	0																								
160°	0	0	0																								
170°	0	0	0																								
180°	0	0	0																								

