

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT223083WW-LD9

効 率	F 	5 %
	F 	95 %
	F 	100 %
	器具 光束	740 lm

保 守 率	良	0.83
	中	0.81
	否	0.77

最大取付間隔		
A-A	1.3	H
B-B	1.2	H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0			
					固有照明率 (×0.01)																							
					室指数																							
0°	304	304	304	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
10°	299	298	299																									
20°	286	281	283																									
30°	263	253	258																									
40°	233	218	226																									
50°	198	176	187																									
60°	159	129	145																									
70°	121	79	103																									
80°	86	30	65																									
90°	58	2	38																									
100°	40	1	20																									
110°	13	1	1																									
120°	0	1	1																									
130°	0	1	0																									
140°	0	0	0																									
150°	0	0	0																									
160°	0	0	0																									
170°	1	0	0																									
180°	1	1	0																									

