

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT223163L-LD9

効 率	F 	5 %
	F 	95 %
	F 	100 %
	器具 光束	1440 lm

保 守 率	良	0.83
	中	0.81
	否	0.77

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反 射 率 (%)	天井		80						70						50						30		20	0					
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50			30			10	0		
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	20	0
室指数				固 有 照 明 率 (×0.01)																													
0°	304	304	304	0.60	60	55	46	43	37	36	58	54	45	43	36	35	43	41	35	34	34	34	29	27									
10°	299	298	299	0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	46	44	44	43	38	36									
20°	286	281	283	1.00	79	71	65	60	55	52	76	69	63	59	54	51	60	57	52	50	50	49	44	42									
30°	263	253	258	1.25	87	77	73	67	63	59	83	75	71	65	62	58	67	63	59	57	57	55	50	48									
40°	233	218	226	1.50	92	81	79	71	69	64	88	79	76	70	67	63	72	67	65	61	62	60	55	52									
50°	198	176	187	2.00	100	87	88	79	79	72	96	85	86	77	77	71	80	75	74	69	70	68	63	60									
60°	159	129	145	2.50	105	90	94	83	86	77	100	88	91	82	84	76	85	79	79	74	75	72	68	65									
70°	121	79	103	3.00	108	93	99	87	91	81	104	91	96	85	89	80	89	82	84	78	79	76	72	69									
80°	86	30	65	4.00	113	96	105	91	99	87	108	94	102	90	96	85	95	86	90	83	85	81	77	74									
90°	58	2	38	5.00	116	98	109	94	104	90	111	96	105	92	100	89	98	89	94	86	88	84	80	77									
100°	40	1	20	10.00	122	102	119	100	115	98	117	100	114	98	111	96	105	95	103	93	96	90	88	85									
110°	13	1	1																														
120°	0	1	1																														
130°	0	1	0																														
140°	0	0	0																														
150°	0	0	0																														
160°	0	0	0																														
170°	1	0	0																														
180°	1	1	0																														

