

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKR230323WW-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	2800 lm

保 守 率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反 射 率 (%)	天井		80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70						50						30						10	0			
						70		50		30		70		50		30		50		30		30		10	0			
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
				室指数	固 有 照 明 率 (×0.01)																							
0°	330	330	330	0.60	61	57	47	45	38	37	60	55	46	44	38	37	45	43	37	36	37	36	31	30				
10°	325	324	324	0.80	74	67	59	55	50	48	71	65	58	55	49	47	56	53	48	47	47	46	41	39				
20°	310	305	307	1.00	81	73	67	62	57	54	78	71	65	61	56	54	63	59	55	53	53	52	47	45				
30°	285	276	280	1.25	89	79	75	69	65	61	86	77	73	68	64	61	70	66	63	60	61	59	54	52				
40°	254	237	245	1.50	94	83	81	74	72	67	91	81	79	73	70	66	75	71	68	65	66	64	59	57				
50°	222	192	204	2.00	102	89	91	82	83	75	99	87	89	80	81	75	84	78	78	73	75	72	68	66				
60°	180	140	165	2.50	107	93	97	86	89	81	103	91	95	85	87	80	90	83	84	78	80	77	73	71				
70°	126	85	113	3.00	111	95	102	90	95	85	107	94	99	88	93	84	94	86	88	82	84	81	77	75				
80°	46	31	54	4.00	116	98	109	94	103	90	112	97	105	93	100	89	99	91	95	87	90	86	83	81				
90°	0	0	0	5.00	119	100	113	97	107	93	114	99	109	96	104	92	102	93	99	91	94	89	86	84				
100°	0	0	0	10.00	125	104	122	102	118	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92				
110°	0	0	0																									
120°	0	0	0																									
130°	0	0	0																									
140°	0	0	0																									
150°	0	0	0																									
160°	0	0	0																									
170°	0	0	0																									
180°	0	0	0																									

