

# 東芝照明器具配光データシート

名称	東芝LED器具
形名	LEKTW423523SN-LS9



効率	F	6 %
	F	94 %
	F	100 %
	器具光束	5000 lm

保守率	良	0.88
	中	0.86
	否	0.81

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	289	289	292
10°	285	285	283
20°	274	268	270
30°	249	239	246
40°	223	208	217
50°	193	170	185
60°	158	130	144
70°	124	89	106
80°	90	49	70
90°	61	5	41
100°	39	2	22
110°	24	0	9
120°	6	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																							
0.60		59	55	45	42	36	35	57	53	44	42	35	34	42	40	34	33	33	33	28	26				
0.80		71	64	56	53	47	45	68	63	55	52	46	44	52	50	44	43	43	42	37	35				
1.00		78	70	63	59	54	51	75	68	62	58	52	50	58	55	50	49	49	47	42	40				
1.25		86	76	72	66	62	58	82	74	69	64	60	57	66	62	58	55	55	54	49	46				
1.50		91	80	77	70	67	63	87	78	75	69	66	62	70	66	63	60	60	58	53	50				
2.00		99	86	87	78	78	71	95	84	84	76	76	70	79	73	72	68	68	66	61	58				
2.50		104	90	93	82	85	76	99	87	90	81	82	75	84	78	78	73	73	70	66	63				
3.00		107	92	98	86	90	80	103	90	94	84	87	79	88	81	82	77	77	74	70	67				
4.00		112	95	104	90	98	86	107	93	100	89	94	84	93	85	88	82	83	79	75	72				
5.00		115	98	109	93	102	89	110	95	104	91	99	88	97	88	92	85	86	82	79	76				
10.00		122	102	118	99	114	97	116	100	113	98	110	95	104	94	102	92	95	89	87	83				

