


# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDG87035YL-LS



効率	F ◐	0 %
	F ◑	100 %
	F ○	100 %
	器具光束	385 lm

保守率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	347		
10°	341		
20°	322		
30°	292		
40°	252		
50°	206		
60°	153		
70°	98		
80°	44		
90°	1		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	1		
170°	1		
180°	1		

反射率 (%)	天井	80						70						50						30						20						0																
	壁	70		50		30		70		50		30		50		30		50		30		30		10		0		0		0																		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10															
室指数	固有照明率 (×0.01)																																															
0.60	62	57	48	46	40	38	61	56	47	45	39	38	46	44	38	38	38	37	33	31																												
0.80	75	68	60	57	51	49	72	66	59	56	51	49	57	55	49	48	48	47	43	41																												
1.00	82	73	68	63	58	55	79	72	66	62	58	55	64	61	56	54	55	53	49	47																												
1.25	90	80	76	70	67	63	87	78	75	69	66	62	71	67	64	61	62	60	56	54																												
1.50	95	83	82	75	73	68	91	82	80	74	72	67	77	72	69	66	67	65	61	58																												
2.00	103	90	92	82	84	76	99	88	90	81	82	76	85	79	79	74	76	73	69	67																												
2.50	108	93	98	87	90	81	104	91	95	86	88	81	90	83	84	79	81	78	74	72																												
3.00	111	96	103	90	96	85	107	94	100	89	93	85	94	87	89	83	85	81	78	76																												
4.00	116	99	109	94	103	91	112	97	106	93	100	90	99	91	95	88	91	86	83	81																												
5.00	119	101	113	97	108	94	114	99	109	96	105	93	103	94	99	91	94	89	87	84																												
10.00	125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92																												

