

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEKR760901JL-LD9



効 率	F ◡	0 %
	F ◒	100 %
	F ○	100 %
器具 光束		6300 lm

保守 率	良	0.81
	中	0.77
	否	0.68

前面	和風カバー (乳白)
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	377	377	377
10°	369	369	369
20°	345	345	345
30°	308	308	308
40°	262	262	262
50°	208	208	208
60°	148	148	148
70°	87	87	87
80°	31	31	31
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射 率 (%)	天井	80						70						50						30		20		0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0							
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0						
室指数	固有照明率 (×0.01)																							
0.60	64	59	50	47	41	40	62	58	49	47	41	40	48	46	40	39	40	39	35	33				
0.80	76	69	62	58	53	51	74	68	61	58	53	51	59	56	52	50	51	50	45	43				
1.00	83	75	70	65	61	58	81	73	68	64	60	57	66	62	58	56	57	56	51	49				
1.25	91	81	78	72	69	65	88	79	77	71	68	64	73	69	66	63	64	62	58	56				
1.50	96	85	84	76	75	70	93	83	82	75	74	69	78	73	72	68	69	67	63	61				
2.00	104	91	94	84	86	78	101	89	91	83	84	78	87	81	81	76	78	75	71	69				
2.50	109	94	100	88	92	83	105	92	97	87	90	82	92	85	86	81	83	80	76	74				
3.00	112	96	104	91	97	87	108	95	101	90	95	86	96	88	91	85	87	83	80	78				
4.00	117	99	110	95	105	92	113	98	107	94	102	91	101	92	97	89	92	88	85	83				
5.00	120	101	114	98	109	95	115	100	110	97	106	94	104	95	100	92	95	90	88	86				
10.00	125	105	122	103	119	101	121	103	118	102	115	100	110	100	108	98	102	96	95	93				

