

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT425253YN-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		2400 lm

保守率	良	0.86
	中	0.81
	否	0.72

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反射率 (%)	天井						壁						50						30		20		0	
θ	φ	A-A	B-B		80						70						50						30		20		0	
0°		329	329	329	天井	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	30	10	0	10	0	0	0
10°		323	322	322	壁	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30
20°		307	303	305	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30
30°		282	273	277	室指数 固有照明率 (×0.01)																							
40°		250	235	242	0.60	61	56	47	44	38	37	60	55	46	44	38	37	45	43	37	36	36	36	31	29			
50°		215	189	200	0.80	73	67	59	55	49	47	71	65	58	54	49	47	56	53	48	46	47	46	41	39			
60°		175	139	160	1.00	81	72	66	61	57	54	78	71	65	61	56	53	62	59	54	52	53	52	47	45			
70°		127	84	112	1.25	88	78	75	68	65	61	85	77	73	67	64	60	70	66	62	59	60	58	54	51			
80°		76	32	62	1.50	93	82	81	73	71	66	90	81	79	72	70	65	75	70	68	64	65	63	59	56			
90°		0	0	0	2.00	102	89	91	81	82	75	98	87	88	80	80	74	84	78	77	73	74	71	67	65			
100°		0	0	0	2.50	107	92	97	86	89	80	103	91	94	84	87	79	89	82	83	78	79	76	72	70			
110°		0	0	0	3.00	111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	76	74			
120°		0	0	0	4.00	115	98	108	94	102	89	111	97	105	92	99	89	99	90	94	87	89	85	82	80			
130°		0	0	0	5.00	118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	88	86	83			
140°		0	0	0	10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91			
150°		0	0	0																								
160°		0	0	0																								
170°		1	1	0																								
180°		1	1	1																								

