

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT415403WW-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		3500 lm

保守率	良	0.86
	中	0.81
	否	0.72

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反射率 (%)	天井	80			70			50			30			20			0		
θ	φ	A-A	B-B		壁	70	50	30	70	50	30	50	30	50	30	30	10	30	10	10	0	0	0
0°		344	344	344	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0
10°		337	337	336	室指数																		
20°		319	318	318	固有照明率 (×0.01)																		
30°		293	288	289	0.60	62	57	48	46	39	38	60	56	47	45	39	38	46	44	38	37	38	37
40°		257	249	252	0.80	75	68	60	57	51	49	72	66	59	56	50	49	57	54	49	48	48	47
50°		215	203	207	1.00	82	73	68	63	58	55	79	72	66	62	58	55	64	60	56	54	55	53
60°		164	152	158	1.25	90	80	76	70	67	63	87	78	75	69	66	62	71	67	64	61	62	60
70°		102	96	102	1.50	95	83	82	75	73	68	92	82	80	74	72	67	77	72	69	66	67	65
80°		27	37	39	2.00	103	90	92	82	84	77	100	88	90	81	82	76	85	79	79	74	76	73
90°		0	2	2	2.50	108	93	98	87	91	82	104	91	96	86	88	81	90	84	85	79	81	78
100°		0	1	1	3.00	112	96	103	90	96	86	108	94	100	89	94	85	94	87	89	83	85	82
110°		0	1	1	4.00	116	99	109	95	103	91	112	97	106	93	101	90	100	91	95	88	91	86
120°		0	1	1	5.00	119	101	113	97	108	94	115	99	110	96	105	93	103	94	99	91	94	89
130°		0	1	1	10.00	125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	101	96
140°		0	1	1																			
150°		0	1	1																			
160°		0	1	0																			
170°		1	1	1																			
180°		1	1	1																			

