

東芝照明器具配光データシート


名 称	東芝LED器具
形 名	LEKT225083N-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		780 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考	
----	--

光度 (cd/1000lm)				反 射 率 (%)	天 井 壁 床	80						70						50						30			20	0						
$\theta \backslash \phi$	A-A	B-B	C-C			70			50			30			70			50			30			50			30			30			10	0
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数					固 有 照 明 率 (×0.01)																													
0°					61	56	47	44	38	37	60	55	46	44	38	37	45	43	37	36	36	36	31	29										
10°					73	67	59	55	49	47	71	65	58	54	49	47	56	53	48	46	47	46	41	39										
20°					81	72	66	61	57	54	78	71	65	61	56	53	62	59	54	52	53	52	47	45										
30°					88	78	75	68	65	61	85	77	73	67	64	60	70	66	62	59	60	58	54	51										
40°					93	82	81	73	71	66	90	81	79	72	70	65	75	70	68	64	65	63	59	56										
50°					102	89	91	81	82	75	98	87	88	80	80	74	84	78	77	73	74	71	67	65										
60°					107	92	97	86	89	80	103	91	94	84	87	79	89	82	83	78	79	76	72	70										
70°					111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	76	74										
80°					115	98	108	94	102	89	111	97	105	92	99	89	99	90	94	87	89	85	82	80										
90°					118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	88	86	83										
100°					125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91										
110°																																		
120°																																		
130°																																		
140°																																		
150°																																		
160°																																		
170°																																		
180°																																		

