

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDS-35113L B-LS1

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	0.8 H
B-B	0.8 H

光源	名称	
	形名	LED
	光束	2900 lm × 1

効 率	F	0%
	F	100%
	F	100%
	器具 光束	2890 lm

備考	
----	--

前面	
反射面	

0°	1325	25°	769
1°		30°	480
2°		35°	239
3°		40°	97
4°		45°	39
5°	1311	50°	22
6°		55°	16
7°		60°	11
8°		65°	5
9°		70°	1
10°	1242	75°	0
11°		80°	0
12°		85°	0
13°		90°	0
14°			
15°	1119		
16°			
17°			
18°			
19°			
20°	978		

反射率 (%)	天井	80				70				50				30	20	0				
	壁	70	50	30	70	50	30	50	30	50	30	30	10	0						
	床	30	10	30	10	30	10	30	10	30	10	30	10	10	0					
室指数	照 明 率 (×0.01)																			
0.60	94	87	86	81	81	78	93	86	85	81	80	78	84	81	80	78	79	77	76	75
0.80	104	95	97	91	92	88	103	94	96	91	91	88	94	90	90	88	89	87	86	85
1.00	107	96	100	92	95	90	105	95	98	92	94	89	96	91	92	89	91	88	87	86
1.25	110	98	103	94	98	92	108	97	101	94	97	91	98	93	95	91	93	90	88	87
1.50	113	99	106	96	101	94	110	98	104	96	99	93	101	94	97	92	95	92	90	89
2.00	117	101	110	99	106	96	113	100	108	98	104	96	104	96	100	95	97	94	92	91
2.50	119	102	113	100	109	98	115	101	111	99	107	97	106	98	103	96	99	95	93	92
3.00	121	103	116	101	111	99	117	102	113	100	109	99	107	99	105	97	100	96	95	93
4.00	123	105	119	103	116	102	119	104	116	102	113	101	110	100	108	99	103	98	96	95
5.00	125	105	121	104	118	103	121	104	118	103	115	102	111	101	109	101	104	99	98	96
10.00	128	107	127	107	125	106	124	106	122	106	121	105	115	104	114	103	108	102	101	99

