

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDD-35043W W

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔		備考
A-A	0.5 H	
B-B	0.5 H	

光源	名称	
	形名	LED
	光束	3360 lm × 1

効 率	F	0%
	F	100%
	F	100%
	器具 光束	3360 lm

前面	
反射面	

0°	3555	25°	341
1°		30°	126
2°		35°	57
3°		40°	40
4°		45°	29
5°	3335	50°	19
6°		55°	13
7°		60°	8
8°		65°	4
9°		70°	1
10°	2603	75°	0
11°		80°	0
12°		85°	0
13°		90°	0
14°			
15°	1862		
16°			
17°			
18°			
19°			
20°	792		

反射率 (%)	天井	80				70				50				30		20		0		
	壁	70		50		30		70		50		30		50		30		10		0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数	照 明 率 (×0.01)																			
0.60	106	98	100	95	96	94	105	97	100	95	96	93	98	95	95	93	95	93	92	91
0.80	114	104	109	102	105	101	113	103	108	102	105	101	106	101	103	100	102	100	99	99
1.00	114	103	109	101	105	99	112	102	107	100	104	99	105	100	102	99	101	98	97	96
1.25	115	102	109	100	104	98	113	101	107	99	103	98	104	98	101	97	99	96	95	94
1.50	116	103	111	100	106	99	114	102	109	100	105	98	105	99	102	97	100	97	95	94
2.00	119	103	113	101	109	99	116	102	111	100	107	99	106	99	103	98	100	97	95	94
2.50	120	104	115	102	111	100	117	103	113	101	109	100	108	100	105	99	101	97	96	95
3.00	122	105	118	103	114	101	118	104	115	102	111	101	109	101	107	99	103	98	97	95
4.00	125	106	121	105	118	104	121	105	118	104	115	103	112	102	101	101	105	100	99	97
5.00	126	107	124	106	121	105	122	106	120	105	118	105	114	103	112	103	107	101	100	99
10.00	130	109	129	109	129	109	126	108	125	108	125	108	118	106	117	107	111	105	104	102

