

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDD-35045W K

保守率	良	0.81
	中	0.77
	否	0.68

光源	名称	
	形名	LED
	光束	2690 lm × 1

効 率	F	0%
	F	100%
	F	100%
	器具 光束	2690 lm

最大取付間隔		備考
A-A	0.4 H	
B-B	0.4 H	

前面	
反射面	

0°	5211	25°	270
1°		30°	103
2°		35°	52
3°		40°	39
4°		45°	29
5°	4676	50°	19
6°		55°	13
7°		60°	8
8°		65°	4
9°		70°	1
10°	2790	75°	0
11°		80°	0
12°		85°	0
13°		90°	0
14°			
15°	1401		
16°			
17°			
18°			
19°			
20°	625		

反射率 (%)	天井	80				70				50				30		20		0		
	壁	70	50	30	70	50	30	50	30	50	30	30	10	0	0	0	0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	0		
室指数	照 明 率 (×0.01)																			
0.60	108	99	102	97	99	96	107	99	102	97	98	96	100	97	98	95	97	95	94	94
0.80	115	105	110	104	107	103	114	104	109	103	106	102	108	103	105	102	104	102	101	101
1.00	115	104	110	102	106	101	113	103	108	101	105	100	106	101	103	100	102	99	98	98
1.25	115	103	110	100	105	99	113	102	108	100	104	98	105	99	102	98	100	97	96	95
1.50	117	103	111	101	107	99	114	102	109	100	105	99	106	99	103	98	100	97	96	95
2.00	119	103	113	101	109	99	116	102	111	100	107	99	107	99	104	98	101	97	95	94
2.50	121	104	116	102	111	101	117	103	113	101	109	100	108	100	105	99	102	98	96	95
3.00	122	105	118	103	114	102	119	104	115	102	111	101	109	101	107	100	103	98	97	96
4.00	125	106	121	105	118	104	121	105	118	104	115	103	112	102	110	102	105	100	99	98
5.00	126	107	124	106	121	106	122	106	120	105	118	105	114	104	112	103	107	102	101	99
10.00	130	109	130	109	129	110	126	108	126	108	125	109	118	107	118	107	111	105	105	103

