

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDG88026YN

保守率	良	0.67
	中	0.63
	否	0.56

光源	名称	LEDランプ
	形名	LDA5L-G-E17 /S/40W
	光束	440 lm × 1

効 率	F $\bigcap$	0 %
	F $\bigcup$	78 %
	F $\bigcirc$	78 %
	器具 光束	345 lm

--	--

最大取付間隔	
A-A	1.13 H
B-B	1.13 H

備考	
----	--

前 面	
反射面	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	438		
10°	427		
20°	386		
30°	322		
40°	268		
50°	166		
60°	40		
70°	0		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		57	53	48	45	42	41	56	52	47	45	42	40	46	44	41	40	41	40	37	36		
0.80		67	61	58	55	53	50	66	60	58	54	52	50	56	54	51	50	51	49	47	46		
1.00		73	65	64	59	58	55	71	64	63	59	57	55	61	58	56	54	55	54	51	50		
1.25		78	69	70	64	64	60	76	68	69	63	63	60	66	62	62	59	60	59	56	55		
1.50		81	72	74	67	68	64	79	71	72	66	67	63	70	65	66	62	64	62	59	58		
2.00		87	75	80	72	75	69	84	74	79	71	74	68	75	70	72	67	69	67	65	63		
2.50		89	77	84	74	79	72	87	76	82	73	78	71	78	72	75	70	72	69	67	66		
3.00		91	78	87	76	83	74	89	77	84	75	81	73	80	74	77	72	74	71	69	68		
4.00		94	80	90	78	87	76	91	79	88	77	84	76	83	76	80	74	77	73	72	70		
5.00		96	81	92	79	89	78	92	80	89	78	87	77	84	77	82	76	78	74	73	71		
10.00		99	82	97	81	95	81	95	81	93	81	92	80	87	79	86	78	81	77	76	74		

