

東芝照明器具配光データシート

| | |
|----|-----------------|
| 名称 | 東芝LED器具 |
| 形名 | LEKR815133W-LS9 |



| | | |
|--------|----------|----------|
| 効 率 | F | 0 % |
| | F | 100 % |
| | F | 100 % |
| | 器具 光束 | 12200 lm |

| | | |
|-------------|---|------|
| 保 守 率 | 良 | 0.86 |
| | 中 | 0.81 |
| | 否 | 0.72 |

| | |
|-----|----------|
| 前面 | カバー (乳白) |
| 反射面 | 塗装 (白) |

| | |
|--------|-------|
| 最大取付間隔 | |
| A-A | 1.3 H |
| B-B | 1.2 H |

備考

| 光度 (cd/1000lm) | | | |
|-------------------------|-----|-----|-----|
| $\theta \setminus \phi$ | A-A | B-B | C-C |
| 0° | 355 | 355 | 355 |
| 10° | 348 | 349 | 348 |
| 20° | 330 | 329 | 328 |
| 30° | 302 | 299 | 298 |
| 40° | 266 | 258 | 259 |
| 50° | 221 | 211 | 213 |
| 60° | 162 | 158 | 160 |
| 70° | 86 | 99 | 98 |
| 80° | 9 | 38 | 22 |
| 90° | 0 | 0 | 0 |
| 100° | 0 | 0 | 0 |
| 110° | 0 | 0 | 0 |
| 120° | 0 | 0 | 0 |
| 130° | 0 | 0 | 0 |
| 140° | 0 | 0 | 0 |
| 150° | 0 | 0 | 0 |
| 160° | 0 | 0 | 0 |
| 170° | 0 | 0 | 0 |
| 180° | 0 | 0 | 0 |

| 反射率 (%) | 天井 | 80 | | | | | | 70 | | | | | | 50 | | | | | | 30 | | 20 | | 0 |
|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|--|----|--|---|
| | 壁 | 70 | 50 | 30 | 70 | 50 | 30 | 70 | 50 | 30 | 50 | 30 | 50 | 30 | 30 | 10 | 0 | | | | | | | |
| 床 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 0 | | | | | | | |
| 室指数 | 固有照明率 (×0.01) | | | | | | | | | | | | | | | | | | | | | | | |
| 0.60 | 63 | 58 | 49 | 46 | 40 | 39 | 61 | 57 | 48 | 46 | 40 | 39 | 46 | 45 | 39 | 38 | 38 | 33 | 32 | | | | | |
| 0.80 | 75 | 68 | 61 | 57 | 52 | 50 | 73 | 67 | 60 | 57 | 52 | 50 | 58 | 55 | 50 | 49 | 49 | 48 | 44 | 42 | | | | |
| 1.00 | 83 | 74 | 69 | 64 | 60 | 57 | 80 | 73 | 68 | 63 | 59 | 56 | 65 | 62 | 57 | 55 | 56 | 55 | 50 | 48 | | | | |
| 1.25 | 91 | 80 | 78 | 71 | 68 | 64 | 88 | 79 | 76 | 70 | 67 | 63 | 73 | 68 | 65 | 62 | 63 | 62 | 57 | 55 | | | | |
| 1.50 | 96 | 84 | 83 | 76 | 74 | 69 | 92 | 83 | 81 | 75 | 73 | 69 | 78 | 73 | 71 | 67 | 69 | 66 | 62 | 60 | | | | |
| 2.00 | 104 | 91 | 94 | 84 | 85 | 78 | 101 | 89 | 91 | 82 | 84 | 77 | 87 | 80 | 80 | 76 | 77 | 75 | 71 | 69 | | | | |
| 2.50 | 109 | 94 | 99 | 88 | 92 | 83 | 105 | 92 | 97 | 87 | 90 | 82 | 92 | 85 | 86 | 81 | 83 | 79 | 76 | 74 | | | | |
| 3.00 | 112 | 96 | 104 | 91 | 97 | 87 | 108 | 95 | 101 | 90 | 95 | 86 | 96 | 88 | 91 | 84 | 87 | 83 | 80 | 78 | | | | |
| 4.00 | 117 | 99 | 110 | 95 | 104 | 92 | 113 | 98 | 107 | 94 | 102 | 91 | 101 | 92 | 97 | 89 | 92 | 88 | 85 | 83 | | | | |
| 5.00 | 120 | 101 | 114 | 98 | 109 | 95 | 115 | 100 | 110 | 97 | 106 | 94 | 104 | 95 | 100 | 92 | 95 | 90 | 88 | 86 | | | | |
| 10.00 | 125 | 105 | 122 | 103 | 119 | 102 | 121 | 104 | 118 | 102 | 116 | 100 | 110 | 100 | 98 | 102 | 97 | 95 | 93 | 93 | | | | |

