


東芝照明器具配光データシート

名称	LED照明器具
形名	LEDH82379NW-LD



効 率	F ◡	9 %
	F ◒	91 %
	F ○	100 %
	器具 光束	5000 lm

保 守 率	良	0.63
	中	0.60
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	278	279	279
10°	275	274	275
20°	264	263	263
30°	245	242	244
40°	218	214	217
50°	183	179	182
60°	142	138	141
70°	99	96	98
80°	58	56	58
90°	29	28	29
100°	16	16	16
110°	13	13	13
120°	12	13	13
130°	12	13	13
140°	13	13	13
150°	12	12	12
160°	12	12	12
170°	12	13	13
180°	13	13	13

反 射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																							
0.60	59	54	45	42	36	35	57	53	44	42	35	34	41	40	34	33	33	32	28	25					
0.80	71	64	56	53	47	45	68	62	55	52	46	44	52	49	44	43	42	41	36	34					
1.00	78	70	64	59	54	51	75	68	62	58	53	50	58	55	50	49	48	47	42	39					
1.25	86	76	72	66	62	58	82	74	70	64	61	57	65	61	58	55	55	53	48	45					
1.50	91	80	78	70	68	63	87	77	75	69	66	62	70	66	63	60	60	58	53	50					
2.00	99	86	87	78	78	72	94	84	84	76	76	70	78	73	72	68	68	65	60	57					
2.50	104	89	93	83	85	77	99	87	90	81	82	75	83	77	77	72	73	70	65	62					
3.00	107	92	98	86	90	81	102	90	94	84	87	79	87	80	82	76	77	73	69	66					
4.00	112	95	105	90	98	86	107	93	100	88	94	84	92	85	88	81	82	78	74	71					
5.00	115	97	109	93	103	89	110	95	104	91	99	88	96	87	92	84	85	81	77	74					
10.00	121	101	118	99	114	97	116	99	112	97	109	95	103	93	100	91	93	88	85	81					

